

# POLYCLIM 2000




## DESCRIPTION

Single block climate regulator with standard and predefined functions

CLI5097



## FUNCTIONS

| Functions   |   | Description   | Number of outputs |
|---|---|---|-------------------|
|  | Ventilation on 2 sides or double roof pitch | Regulation proportional to ambient temperature<br>Weather protection (wind, rain)<br>Outside influences (wind, wind vane, outside temperature, sunshine)<br>24-hour temperature integration | 4                 |
|  | Inflation                                   | Fan operation management by cue and difference<br>Outside influence (wind speed)  | 1                 |
|  | Alarm                                       | Activation on an exceeded high or low threshold (temperature or humidity) or regulator operating fault (network, sensors disconnected, etc.).<br>Output normally closed on power up         | 1                 |

# POLYCLIM 2000

## THE SUPPLIED INDOOR SENSOR



## COMPATIBLE WEATHER SENSORS

| Photo   | Ref               | Measurement    | Signal      | Range        |
|---|-------------------|----------------|-------------|--------------|
|  | Wind vane sensor  |                |             |              |
|   | CAP0022           | Wind direction | Dry contact | 2 directions |
|  | Wind sensor       |                |             |              |
|   | CAP0021           | Wind speed     | Frequency   | -            |
|  | Rain gauge sensor |                |             |              |
|   | CAP0030           | Rain detection | DISCRETE    | -            |